

DICC35

CONDUCTIVITY CONTROLLER



SIZE : 96 X 96



SENSOR 0.01K/0.1K/1k

SPECIFICATIONS

POWER	: 220~240VAC , 50HZ
CONDUCTIVITY RANGE	: A)0~10uS B)0~20ms
CONDUCTIVITY RESOLUTION	: A)00~0.01uS B)0~0.1mS
CONDUCTIVITY ACCURACY	: A) 0.1us B) 0.1ms
TEMPERATURE RANGE	: 0~150 C
TEMPERATURE RESOLUTION	: 0.1C
TEMPERATURE ACCURACY	: 0.5C
CONDUCTIVITY DIGITAL OUTPUT	: 5A, 1CO, RELAY
CONDUCTIVITY ANALOG OUTPUT	: 4~20mA
CONDUCTIVITY COMMUNICATION	: RS232 Modbus RTU [OPTIONAL]
CELL CONSTANT	: 0.01K / 0.1K / 1K
DISPLAY	: 3.5 COLOUR
BODY	: ABS
OUTER DIMENSIONS	: 96x96x110mm



T 6, DHARMADEV NAGAR, OPP. SAMARAT NAGAR, ISANPUR, AHMEDABAD-382443, GUJARAT.

www.datainstrumentsindia.com, E-mail : utkarsh@datainstrumentsindia.com, Ph (M) 09909035088,093 288 88 879.